

Standalone Panel Antenna

2.3-2.5GHz 16dBi



- ◆ High gain, cost effective patented circuit design
- ◆ Low profile and rugged design for outdoor use
- ◆ US Engineered
- ◆ Manufactured under strict US quality control procedures
- ◆ Articulating wall/pole bracket (BRA-A-1699-02) included
- ◆ Custom designs available


Mechanical and Environmental Specifications	
Length x Width x Depth	10.4in x 10.4in x .49in (26.4cm x 26.4cm x 1.2cm)
Weight	1.3lb (0.59kg)
Backplane	Aluminum
Radome	UV stabilized ABS plastic, gray
Wind Survivability	125mph (201kph)
Wind Load	0.75ft ² (0.069m ²)
Operating Temperature Range	-49°F to +149°F (-45°C to +65°C)
Pole Mount Diameter Range	0.75in to 3.0in (1.9cm to 7.6cm)

Electrical Specifications	
Frequency Range	2.3-2.5GHz
Gain	16.0 dBi typical
3dB Beamwidth Vertical/Horizontal	25deg/27deg
Polarization	Single linear, horizontal or vertical
VSWR	≤1.5:1 typical, 1.7:1 max
Front-to-Back Ratio	≤30 dB
Cross Polarization	≤20 dB
Power Rating	6 watts
Impedance	50 ohms
Lightning Protection	DC ground
Connector Type	N Jack


Ordering Information	
Part #	Description
ARC-PA2416B01	2.3-2.5GHz 16dBi, N Jack

Shipping Information	
Sizes and Weights	Description
TBD	Packaging includes 10 units in a single over pack box w/ brackets

RF Patterns
Vertical Cut, typ.



RF Patterns
Horizontal Cut, typ.



www.antennas.com

Don't see what you need? Contact us to discuss alternate configurations.

Specifications subject to change without notice.
See www.antennas.com for warranty information