

# Standalone Panel Antenna

## 5.15-5.875GHz 20dBi



- ◆ High gain, cost effective patented circuit design
- ◆ Low profile and rugged design for outdoor use
- ◆ US Engineered
- ◆ Manufactured under strict US quality control procedures
- ◆ Articulating wall/pole bracket (BRA-A-1699-02) included
- ◆ Custom designs available


Mechanical and Environmental Specifications	
Length x Width x Depth	10.4in x 10.4in x .49in (26.4cm x 26.4cm x 1.2cm)
Weight	1.43lb (0.65kg)
Backplane	Aluminum
Radome	UV stabilized ABS plastic, gray
Wind Survivability	125mph (201kph)
Wind Load	0.75ft <sup>2</sup> (0.069m <sup>2</sup> )
Operating Temperature Range	-49°F to +149°F (-45°C to +65°C)
Pole Mount Diameter Range	0.75in to 3.0in (1.9cm to 7.6cm)

Ordering Information	
Part #	Description
ARC-PA5820B01	5.8GHz 20dBi, low profile radome, N Jack

Shipping Information	
Sizes and Weights	Description
TBD	Packaging includes 10 units in a single over pack box w/ brackets

Electrical Specifications	
Frequency Range	5.15—5.875 GHz
Gain	20dBi
3dB Beamwidth Vertical/Horizontal	14 degrees/11 degrees
Polarization	Single linear, horizontal or vertical
VSWR	≤1.5:1 typ., ≤1.7:1 max.
Front-to-Back Ratio	≤35 dB
Cross Polarization	≤20 dB
Power Rating	6 watts
Impedance	50 ohms
Lightning Protection	DC ground
Connector Type	N Jack

RF Patterns  
Vertical Cut, typ.



RF Patterns  
Horizontal Cut, typ.

