

Specifications Sheet



Motorola Canopy

900 MHz AP Connectorized (External antenna)



| | |
|--|--|
| Canopy Part Number | 9000APC |
| Description | 900 MHz AP Connectorized (External antenna) |
| Signaling Rate | 6 Mbps maximum |
| Typical LOS Range | 40 Miles (64 km) |
| Typical Aggregate Useful Throughput | 4 Mbps max |
| Frequency range of band | ISM 902-928 MHz |
| Non-overlapping Channels | 3 |
| Channel Width | 8 MHz |
| Modulation Type | High Index 2-level and 4-level Frequency Shift Keying (FSK) optimized for interference rejection |
| Channel Spacing | 1 MHz |
| Encryption | DES capable |
| Latency | < 15 msec |
| Carrier to Interference ratio (C/I) | -3dB @ 3 Mbps, -10dB @ 6 Mbps at -70dBm |
| Nominal Receiver Sensitivity (dbm typical) | -90 dBm |
| Antenna Gain (dB) | varies |
| EIRP (dB) | 36 dBm |
| Equivalent Isotropic Radiated Power (EIRP) | 4 W |
| DC Power (typical) | 0.3 A @ 24 VDC = 7.2 W |
| Antenna Beam Width | Connectorized 60 degree beam width azimuth and 35 degree elevation -12.5 dBi |
| Mean Time Between Failure (MTBF) | 40 yr |
| Temperature | -40° C to +55° C (-40° F to +131° F) |
| Wind Survival | 190 km/hr (118 miles/hr) |
| Dimensions | 11.75 in H x 3.4 in W x 3.4 in D (29.9 cm H x 8.6 cm W x 8.6 cm D) Antenna Varies |
| Weight | .45 kg (1 lb), antenna varies. |
| Access Method | Time Division Duplexing/Time Division Multiple Access (TDD/TDMA) |
| Interface | 10/100 Base T, half/full duplex. Rate auto negotiated (802.3 compliant) |
| Protocols Used | IPV4, UDP, TCP, ICMP, Telnet, HTTP, FTP, SNMP |
| Network Management | HTTP, TELNET, FTP, SNMP Version 2c |
| FCC ID | ABZ89FC5809 |
| Industry Canada Certification Number | 109W-9000 |

Specifications subject to change without notice.

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their respective owners. © Motorola, Inc. 2007